

Sušači peškira "Elegant"



Grejanje

Priključak 4 x 1/2"

Cevasti sušači:

L (širina) mm	H (visina) mm	Razmak između osa mm	Broj elemenata	Zapremina vode l	Težina* kg	Toplotna moć 75/65°C-20°C W
400	800	355	15	3,04	3,98	288
400	1000	355	17	3,62	4,71	339
400	1200	355	21	4,40	5,75	414
400	1600	355	28	5,87	7,66	553
500	800	455	15	3,53	4,62	344
500	1000	455	17	4,17	5,46	403
500	1200	455	21	5,09	6,65	493
500	1600	455	28	6,79	8,67	657
600	800	555	15	4,02	5,26	400
600	1000	555	17	4,73	6,18	466
600	1200	555	21	5,78	7,56	571
600	1600	555	28	7,70	10,07	762

* Težine za proizvod date su od strane proizvođača. Stvarne težine mogu odstupati od ovih vrednosti u zavisnosti od tolerancije samog proizvođača.

Nosač sušača peškira



Namena: Pričvršćivanje sušača peškira.

Osobine: Pozicije su urađene od ABS polymera.

- Konstrukcija proizvoda omogućava univerzalnu i široku primenu za sve tipove sušača peškira, ravne i rondo, takođe za različite prečnike cevi Ø 20, 22 i 25;
- Omogućena korekcija podešavanja u montaži po visini 20 mm i po dubini 20 mm;
- Proizvod je sastavljen od pet ABS delova i dva kompleta (vijak+matica);
- Normativ utroška: 3-4 komada po radijatoru.

Dimenzije: 82x28x43,5 mm

Boja: Bela/hromirano/crna

Pakovanje: 100/400



L (širina) mm	H (visina) mm	Broj elemenata	Težina* (kg)		Toplotna moć 75/65°C-20°C W	
			ravni	zaobljeni	ravni	zaobljeni
400	700	12	4,3	4,3	250	250
400	800	15	5,2	5,2	301	301
400	1000	18	6,3	6,3	367	367
400	1100	20	7,0	7,0	406	406
400	1200	22	7,6	7,6	444	444
400	1400	24	8,6	8,6	498	498
400	1500	26	9,2	9,2	536	536
400	1600	28	9,9	9,9	575	575
400	1800	30	10,8	10,8	629	629
500	700	12	5,0	5,0	296	296
500	800	15	6,0	6,0	359	359
500	1000	18	7,3	7,3	436	436
500	1100	20	8,0	8,0	483	483
500	1200	22	8,8	8,8	530	530
500	1400	24	9,9	9,9	590	590
500	1500	26	10,6	10,6	637	637
500	1600	28	11,4	11,4	684	684
500	1800	30	12,5	12,5	745	745
600	700	12	5,6	5,6	343	343
600	800	15	6,8	6,8	417	417
600	1000	18	8,2	8,2	506	506
600	1100	20	9,1	9,1	560	560
600	1200	22	10,0	10,0	615	615

Technical drawing of a mechanical part, showing three views: front view, top view, and bottom view.

Front View: Shows a rectangular part with a central slot. Dimensions include a total width of 40, a central slot width of 30, and a slot depth of 30. The part is divided into two sections, A-A and B-B, with a centerline indicated.

Top View: Shows the part from above, with a central slot. Dimensions include a total width of 40, a central slot width of 30, and a slot depth of 30. The part is divided into two sections, A-A and B-B, with a centerline indicated.

Bottom View: Shows the part from below, with a central slot. Dimensions include a total width of 40, a central slot width of 30, and a slot depth of 30. The part is divided into two sections, A-A and B-B, with a centerline indicated.

Section A-A: A cross-section view showing the internal structure of the part, including a central slot and a central hole. Dimensions include a total width of 40, a central slot width of 30, and a slot depth of 30.

Section B-B: A cross-section view showing the internal structure of the part, including a central slot and a central hole. Dimensions include a total width of 40, a central slot width of 30, and a slot depth of 30.

Technical drawing of a metal grate (Grat) showing side and top views. The side view shows a rectangular frame with horizontal bars, labeled with dimensions 40, A, and 30. The top view shows a semi-circular end profile with a diameter of 40 and a central opening of 22. A curved arrow indicates a 105° angle.

* Težine za proizvod date su od strane proizvođača. Stvarne težine mogu odstupati od ovih vrednosti u zavisnosti od tolerancije samog proizvođača.